

Experimental Study on Factors Affecting the Recovery of Nickel from Spent Catalyst

Chemical Engineering Department, Collage of Engineering, University of Nahrain, Iraq

Athraa BA, Chemical Engineering Department/Collage

90.C, S:L 1:10 (:) , 40% .. , . . 50

...
...
...

3. I. ...

... F ...
... A ...
... A ...
... 94.3% ... 89.6% ...
... 3 ...

3. I. ...

I ... F ...
... 80 C ... 600 ...
...
...
...



10. Sahu KK, Agarwal A, Pandey BD (2005) Nickel recovery from spent nickel catalyst. Waste management and research 23: 148-154.

11.

1. Sahu KK, Pandey BD, Chand P (2004) Process for recovery of nickel from spent
2. Hubred GL (1985) Leaching nickel, cobalt, molybdenum, tungsten, and vanadium from spent hydroprocessing catalysts. Chevron Research Company. US Patent 4,514,368.
3. Henry E (1965) Method for the recovery of metal values from a spent hydrocarbon conversion catalyst. Sinclair Research Inc. US Patent 3,180,706.
4. handling and utilization. Journal of hazardous materials 101: 123-132.
5. Llanos ZR, Provoost GF, Deering WG, Debaene FJ (1997) Integrated process for the recovery of metals and fused alumina from spent catalysts. Gulf Chemical & Metallurgical Corporation. US Patent 5,702,500.
6. of spent Ni-Mo/Al₂O₃ hydro-processing catalyst. Hydrometallurgy 98: 192-195.
7. Marcantonio PJ (1990) Leaching cobalt, molybdenum, nickel, and vanadium from spent hydroprocessing catalysts. Chevron Research Company. US Patent 4,927,794.
8. Angelidis TN, Tourasanidis E, Marinou E, Stalidis GA (1995) Selective dissolution of critical metals from diesel and naphtha spent hydrodesulphurization catalysts. Resources, conservation and recycling 13: 269-282.
9. Al-Mansi NM, Monem NA (2002) Recovery of nickel oxide from spent catalyst. Waste management 22: 85-90.